


Linea DF V1190	Technical data sheet	
	Version 12/2024	

HEATING & TECHNICAL PARAMETERS:		
energy efficiency class	A-B-C-D-E-F-G	A
direct heat output (nominal power)	[kW]	20,7
heating power range	[kW]	A
energy efficiency index	[EEI]	20,7
energy efficiency at nominal heat output	[%]	A
seasonal space heating energy efficiency	[%]	20,7
CO emission at 13% O ₂	[%]	A
	[mg/Nm ³]	20,7
dust emission at 13% O ₂	[mg/Nm ³]	A
OGC at 13% O ₂	[mg/Nm ³]	20,7
NO _x emission at 13% O ₂	[mg/Nm ³]	A
flue gas mass flow	[g/s]	20,7
average smoke temperature at smoke outlet	[°C]	A
minimum chimney draft	[Pa]	20,7
DIMENSIONS & WIGHT		
total dimensions, height x width x depth	[mm]	1735x1090x630
fascade dimensions, width x height	[mm]	938 x 746
front glass dimensions, width x height	[mm]	904 x 700
maximum log lenght	[cm]	80
smoke flue diameter	[mm]	230 / 240
air inlet diameter	[mm]	123
weight	[kg]	450
CERTIFICATES AND NORMS		
EN 13229	V / -	3185 B9 20
declaration of the Ecodesign requirements	V / -	V
BlmSchV level 2	V / -	V
15a BVG	V / -	
ADDITIONAL INFORMATION		
minimum cross-section of supply air grating	[cm ²]	1030
minimum cross-section of outgoing air grating	[cm ²]	1450
for continous burning	V / -	V
type of fuel		wood logs with moisture content ≤ 20 %
ashpan	V / -	V
appliance suitable for low energy and passive	V / -	V
door opening		up/down + side
possibility of burning with open door	V / -	V
warranty	years	5



All dimensions are approximate

*direct air inlet - optional equipment